Simple Patrol Guard Tour Solution

Are you looking for an affordable yet tough and reliable Guard Tour product then we have the solution for you.

As the name suggest the **Simple Patrol management software** is easy to install and simple to use and yet will provide you with detailed reporting at all levels.

- Reports can be customized to include your company name and logo
- Customer site details are recorded in the database
- Events and incidents can be recorded against a checkpoint location
- Security guards can have a Logon tag and reports will display the Guards name for the duration of their shift
- The administrator can setup user profiles that allow operator Logins with specific access rights (full access – reports only or downloading of wands)
- Full Reporting giving you and your clients confidence that tours are being completed or highlight areas of concern
- Reports can be printed or saved in a variety of formats PDF, CSV and JPEG
- Plus much more

Maximus Technologies Limited   Phone: 0064 4 567-5200   Fax: 0064 4 5670600
Email: sales@maximus.co.nz
WEB: www.maximus.co.nz

K5100 Simple Touch Guard Tour Wand

The **K5100 Guard tour Wand** has been designed to be tough and durable. The USB Downloader is the method used to transfer the checkpoint information from the wand to the Simple Patrol software for viewing.

Features

Anti- vandal

- Over Voltage (AC35v), Over Voltage recording
- Static proof
- Impact Detection
- Read head short circuit Protection
- Reverse-battery Protection
- Super durable (stainless steel body, rubber out shell, PCB sealed box)
- Waterproof.
- 15m (49.22ft) Drop test
- Circuit Shockproof Design

Anti-spamming
- Battery Disconnect Record
- Change time record
- Store up to 120,000 records

Easy maintenance repair and operation
- Low Battery Indicator
- 120,000 records in circulation
- 3 AAA size alkaline batteries

K5100 Guard reader Technical Specifications

Casing	Stainless Steel Body with rubber out shell
Water proof	Water Resistant
Battery used	3 AAA size alkaline batteries
Read Type	iButton
Indicators	Shake and LED
Memory storage	120, 000 records
Size(L×W×H)	147*36*38(mm)
Operating range	-40℃ to +85℃/- 40 F to185 F